

DAIHAN® Compact Multifunction Mixer/Rocker "MIXM", Smoothly Rocking Motion, 24rpm

With Rubber Cushion Platform, Continuous Operation, Ideal for Dishes($\geq \phi 100\text{mm}$) or 1.5~50ml Tubes, 소형 다기능 믹서/락커

2-Year Warranty

- Supplied by DAIHAN Korea
- Quality Certification : ISO 9001.
- Ideal for Dishes($\geq \phi 100\text{mm}$) and 1.5 ~ 50ml Tubes.
- Capacity ; 3ea - $\phi 100\text{mm}$ Dishes, 30ea - 1.5ml Microtubes, 15ea - 15ml Tubes, or 8ea - 50ml Tubes.
- Easy to load and unload the Test Tubes without Turning the Mixer Off.
- Rubber Cushion preventing the Test Tubes from Slipping.
- * Widely used in Hematology, Chemistry, Research and Bacteriology Laboratories.
- * Smooth, Steady, Quiet, and Continuous Operation
- * Rocking Angle : 23°
- * Speed : 24rpm at 60Hz / 20rpm at 50Hz
- * Platform Dimension : w300 x d115 mm <L1>
- * Overall Dimension & Weight(N.W./G.W.) : 350 x 140 x h110 mm, 1.5 / 2.0 kg

DH.MixM0100 Compact Mixer/Rocker, "MIXM-100", for 230V
 DH.MixM0101 "MIXM-101", for 120V

Ea.	Price, ₩
	387,000
	387,000

DAIHAN® Programmable Digital Rocker "RK", Digital Feedback Control, 5~50 rpm, with Certi. & Traceability

With 290 x 200mm or 300 x 300mm Platform with Non-slip Rubber Mat, Smooth Start & Wave Motion, Tilt Angle $\pm 6^\circ / \pm 9^\circ$

디지털 락커, 디지털 피드백 컨트롤 시스템, 부드러운 시동 동작 및 속도 조절

CE 5~50rpm

2-Year Warranty



Back-light LCD

Patented Jog-Shuttle Control System



(1) 290 x 200 mm Rocker "RK-1D" with Included Platform

- Supplied by DAIHAN Korea
- CE Certified
- PL(Product Liability) Insurance
- Stainless-steel Platform Comes with Gray Nonslip Rubber Mat
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- High Precision Digital Speed Control : 1rpm
- Patented Jog-Shuttle Control System
- * Gel Staining, Destaining, Blotting
- * Cell Culture, Hybridization, Washing
- * Programmable Operation Mode Supported : 10 Steps and 6 Programs
- * Digital Timer : Max. 99hr 59min.
- * Alarm Function : Error Status and Timer-end
- * Digital LCD with Back-Light Function for Timer, RPM and Power Bar-Graph
- * Smooth Start and Change of Rocking Speed
- * Overload Protection Function for Motor
- * Storage Function for Set Values : RPM and Timer
- * Stackable Platform with Pad to Double Mixing Area (Optional)
- * Locking Mode supported for Experimental Safety (Input to Jog-Shuttle can be Disabled)

Specifications & Ordering information

<L1>

Spec.		Model	(1) "RK-1D" Platform Size 290 x 200 mm	(2) "RK-2D" Platform Size 300 x 300 mm
Dimensions (w x d x h)	Platform (mm)		290 x 200	300 x 300
	Overall (mm)		290 x 240 x h150	300 x 330 x h150
Speed Range (rpm)			5 ~ 50	
Angle (degree)			± 6 or ± 9 (± 9 as Factory Default)	
Motor			14W Geared DC Motor	
Program Function			10 Steps, 6 Programs	
Timer & Alarm			99hr 59min (with Continuous run.), Error status & Timer-end	
Display			Digital LCD with Back-Light Function	
Controller			Programmable Digital Feedback Controller with Jog-Shuttle Switch(Turn+Push)	
Safety Circuit			Overload Protector for motor	
Platform (Included)			290 x 200mm Platform	300 x 300mm Platform
Others			PL(Product Liability) Insurance Smooth Start and Change of the Stirring Speed for Stable Running Storage Function (RPM, Timer) Locking Mode (Jog-Shuttle Input Disabled) Alarm (Error Status and Timer-end)	
Packing Dimension (w x d x h) (mm)			450 x 350 x 250	
Gross Weight			7 kg	8 kg
Power Consumption			35 W	
Electrical Reqt.s.			Free Voltage (1 Phase, AC 80V~240V, 50/60Hz)	
Cat. No.	230V		DH.WRK01010	DH.WRK01020
	120V		DH.WRK02010	DH.WRK02020
Price, Each. ₩			514,000	535,000

* Other Specifications are available upon Customer's Request.

Optional Second Platform

- DH.WRK05011 Second Platform, "RK5011", for "RK-1D", w290 x d200, with 4 Pillars(L120mm)
- DH.WRK05021 Second Platform, "RK5021", for "RK-2D", w300 x d300, with 4 Pillars(L120mm)

Ea.	Price, ₩
	45,000
	50,000

Second Platform
"RK5021"(Optional)

Pillars

2-Year Warranty

(2) 300 x 300 mm Rocker "RK-2D"
with Second Platform(Optional)